SE-1201 Twelve-channel ECG Mounting Solution



colling stand

Specification

	SE-1201
Input Circuit	Defibrillator protect
Lead	Standard 12 leads
A/D Resolution	24 bits
Time Constant	≥3.2s
Frequency Response	0.05Hz~150Hz (-3dB)
Sensitivity	2.5, 5, 10, 20, 10/5, AGC (mm/mV)
Input Impedance	≥50M (10Hz)
Input Circuit Current	≤0.01µA
Input Voltage Range	≤±5mVpp
Calibration Voltage	1mV±2%
DC Offset Voltage	±600mV
Noise	≤12.5µVp-p
Filter	AC Filter: On/Off DFT Filter: 0.05Hz/0.15Hz/0.25Hz/0.32Hz/0.5Hz/0.67Hz EMG Filter: 25Hz/35Hz/45Hz/OFF LOWPASS Filter:150Hz/100Hz/75Hz
CMRR	≥115dB
Working Mode	Auto/Manual/Rhythm/R-R/Off
Rhythm	Single channel or three channels selectable
Power Supply	AC: 100V-240V, 50/60Hz
Battery	Built-in rechargeable Lithium battery For 200 copies ECG printing
Printer	Thermal printer/External printer
Record Paper	Half A4 size paper (Z-fold)
Record Speed	5mm/s, 6.25mm/s, 10mm/s, 12.5mm/s, 25mm/s, 50mm/s (±3%)
Dimension	361mm×262mm×135mm
Weight	4.2kg
Display	800×480 dots TFT LCD Screen
Communication Interface	Ethernet/USB/SD card slot

EDAN

Edan Instruments, Inc.

- 3/F B, Nanshan Medical Equipment Park, Nanhai Rd 1019#, Shekou, Nanshan Shenzhen, 518067 P.R. China
- Tel: +68-755-26898326 Fax: +86-755-26898330 www.edan.com.cn Email: info@edan.com.cn
- All rights reserved. Features and specifications are subject to change without notice







SE-1201
Twelve-channel ECG







EDAN

SE-1201

Twelve-channel ECG



User-friendly Design

- 12 channel ECG with compact and portable design
- 7" color LCD display with touch screen function
- Alphanumeric keyboard

Streamlined Workflow

- One-touch operation including gender and age-group shortcuts
- Support barcode scanner to simplify workflow

Accurate Clinical Performances

- Weak signal detection with the most advanced 24 bits A/D converter technology
- Anti-noise technology with comprehensive filters and the high CMRR over 115dB
- 120s real-time ECG waveforms freezing and review to assist your diagnosis
- Automatic measurements and interpretation tested by CSE/AHA/MIT database
- Extend printing once arrhythmia is detected to further your rhythm analysis

Flexible Printing Solutions

- Built-in high resolution thermal recorder
- External USB printer support

Data Management

- 200 ECGs internal memory which can be enlarged by USB flash disk and SD card
- Smart ECG Viewer software for data management on PC (option)

Extensive Communications

- DATA transmitting to PC via LAN/WIFI
- Standard ECG formats: PDF, SCP and FDA-XML data export (option)
- Bi-directional data communication with DMS





