

VitaScan LT Bladder Scanner System (Commercial Grade)

VitaScan LT C5

Part Number: 100525C5

Includes:

VitaScan LT Bladder Scanner with Carrying Case
Commercial Grade Tablet (Software Pre-installed)
VitaScan LT Rolling Medical Cart
Fixed-Height, Handle Grip, Scanner Probe Holder, Ultrasound Gel Holder,
Disinfectant Wipes Holder, Medical Grade Power Strip

(1) Bottle Ultrasound Gel

Lifetime Training

Two-Year Limited Warranty

Exclusive Features

The simple-to-use and intuitive VitaScan LT quickly and automatically measures urinary volume and post void retention (PVR). You do not need to be a sonographer or have prior ultrasound experience to succeed with the VitaScan LT.

Real-Time Imaging – View the bladder real-time on 10" backlit touch screen before scanning. Software automatically tracks and outlines the bladder for you.

USB Powered Probe – Draw your power from the Tablet and stop replacing batteries. Stay current with software upgrades.

Single Position Multi-plane Scan – One press of a button automatically displays images of both the sagittal and transverse views.

Fully Automatic Measurements - Automatically calculates and displays bladder volume and PVR. Allows for manually recalculating test results.

And that's not all....

Print to existing printers – Wi-Fi or Bluetooth Printing to your existing printers. Thermal paper is a thing of the past!

Save tests in real-time to local or network folder – Save time by automatically saving the results where you want them the first time around.

Attach results to EMR/EHR - Transfer results to EMR/EHR

Lower cost of ownership – Excellent and affordable extended warranty and support programs available.

Optional Accessories

Antimicrobial Keyboard and Keyboard Tray (#VUSKBKC)

Accessory Basket (#VUS125)

VitaScan LT Calibration Tank (#100651)



Scanner Probe:

Volume range	0 – 1000 ml
Accuracy.....	+/- 10 % of reading, +/- 20 ml
Frequency.....	2.35 MHz
Scanning method.....	sector, 180 degrees
Rotation positions.....	6, 12 or 24 rotating positions
Sweep angle.....	110 degrees
Max detection depth.....	100, 160 or 230 mm
Dimension (LxWxH).....	5.5 x 1.8x 2.6 inches
Probe Weight (incl. cable).....	13.44 ounces
Power Consumption.....	2.5W supplied by USB
Storage temperature.....	-22°F to +122°F
Operating conditions	+50°F to + 113°F, 10% - 80% relative humidity

Commercial Grade Tablet:

10.1" LED Backlit Multi-touch Widescreen, Intel® Quad-Core Processor, 2GB LPDDR3 RAM, 64GB Solid State Memory, Windows 8.1, VitaScan Software Pre-installed

VITACON.

VITACON US

5557 Pioneer Creek Drive, Maple Plain, MN 55359
(800) 757-8450 | sales@Vitacon.us | www.Vitacon.us

January 2015