# Welch Allyn Pocket LED & Pocket Plus LED Ophthalmoscope

Pocket LED

**Pocket Plus LED** 

### **Product Specifications:**



	Ophthalmoscope	Ophthalmoscope	
Model Numbers	12870-BLK, 12870-WHT, 12870-PUR, 12870-BLU	12880-BLK, 12880-WHT, 12880-PUT, 12880-BLU	
Total Height	17.5 cm	17.5 cm	
Head Width	3.0 cm	3.0 cm	
Head Depth	2.8 cm	2.8 cm	
Handle Diameter	2.1 cm	2.1 cm	
Weight Head and Handle (no batteries)	2.5 oz	2.5 oz	
Battery Type	AA Alkaline x 2	AA Alkaline x 2	
Battery Life	>5 hrs	>5 hrs	
Lamp Type	SureColor LED	SureColor LED	
Lamp Life	10,000 to 20,000 hours	10,000 to 20,000 hours	
Efficiency	1.8	1.8	
Diopter Range	'-20 to +20	'-20 to +20	
Diopter Steps	'-20, -15, -10, -8, -6, -4, -3, -2, -1, 0, 1, 2, 3, 4, 6, 8, 10, 15, 20	'-20, -15, -10, -8, -6, -4, -3, -2, -1, 0, 1, 2, 3, 4, 6, 8, 10, 15, 20	
Filter Types	Red-free, Cobalt Blue	Red-free, Cobalt Blue, Neutral Density	
Aperture Spot Sizes	5 (Small, Medium, Large, Slit, Fixation)	5 (Small, Medium, Large, Slit, Fixation)	
Total Flux Large Aperture (Ims, Andor)	.2 to .45 lumens	.2 to .45 lumens	
Field of Illumination/ Distribution, large aperture	11.4 mm at 50 mm distance	11.4 mm at 50 mm distance	
UV/VIS/IR at FO (% from SPD, Optronic)	0%/98.68%/1.32%	0%/98.68%/1.32%	
User Contact Temperature	8°C over ambient max.	8°C over ambient max.	



#### **Available Color Options:**

Onyx, Blueberry, Plum, Vanilla

## Welch Allyn Pocket LED & Pocket Plus LED Otoscope

Product Specifications:	Pocket LED Otoscope	Pocket Plus LED Otoscope
Model Numbers	22870-BLK, 22870-WHT, 22870-PUR, 22870-BLU	22880-BLK, 22880-WHT, 22880-PUR, 22880-BLU
Total Height	16.8 cm	16.8 cm
Head Width	3.0 cm	3.0 cm
Head Depth	5.1 cm	5.1 cm
Handle Diameter	2.1 cm	2.1 cm
Weight Head and Handle (no batteries)	2.53 oz (71.7 grams)	2.53 oz (71.7 grams)
Battery Type	AA Alkaline x 2	AA Alkaline x 2
Battery Life	>5 hrs	>5 hrs
Lamp Type	SureColor LED	SureColor LED
Lamp Life	10,000 to 20,000 hours	10,000 to 20,000 hours
Light Transmission	Fiber Optic	Fiber Optic
Efficiency (lumens/watt,	10.3	10.3
Magnification Power	3.4X	3.4X
Diopter	13.6	13.6
Working Distance w/Specula (visual, best focus dist,	6.5 mm from 4 mm speculum tip	6.5 mm from 4 mm speculum tip
Resolution w/Specula (visual, lp/mm,	3 - 6 lp/mm at working distance	3 - 6 lp/mm at working distance
Depth of Focus w/Specula (visual,	0 to 11 mm from speculum tip	0 to 11 mm from speculum tip
Focal Length	73.45 mm (2.9 in)	73.45 mm (2.9 in)
Field of Illumination/Distribution at FC	34.1 mm @ 50 mm distance from tip	34.1 mm @ 50 mm distance from tip
UV/VIS/IR at FO (% from SPD, Optronic,	0%/99.47%/0.53%	0%/99.47%/0.53%
Total Flux at FO (Ims, Andor,	2.66 lumens	3.62 lumens
Intensity as FO (lux, FC, UDTS370/263 photometer,	1240 lux with 4 mm specula	1540 lux with 4 mm specula
User Contact Temperature	8°C over ambient max.	10°C over ambient max.
Pneumatic Otoscopy Port	Yes	Yes
Pneumatic Otoscopy Sea	Yes	Yes



For more information on the Welch Allyn Pocket LED and Pocket Plus LED Otoscope and Ophthalmoscope, please contact your local distributor or Welch Allyn at 1.800.535.6663.